

Product Showcase

PROCON ROTARY VANE PUMPS



MADE FOR:
Coffee Machines
Autoclaves
Sterilizers
Washing Machines
& More



COFFEE & ESPRESSO ■ WATER TREATMENT ■ BEVERAGE ■ PAINT & INK ■ INDUSTRIAL

BRASS

SERIES 2 | 102A140F11PA

Body Material:
Brass
Port Size:
NPT 3/8"
Flowrate (GPH) / (LPH)
140 / 425
Sealing Material:
EPDM/Nitrile
Maximum Operating Pressure:
150 PSI
Valve Configuration:
Standard-Non External Adjust



SERIES 4 | 104B330F11XX

Body Material:
Brass
Port Size:
NPT 1/2"
Flowrate (GPH) / (LPH)
330 / 1000
Sealing Material:
EPDM/Nitrile
Maximum Operating Pressure:
250 PSI
Valve Configuration:
No Relief Valve



SERIES 4 | 104E240F11XX

Body Material:
Brass
Port Size:
NPT 1/2"
Flowrate (GPH) / (LPH)
240 / 725
Sealing Material:
EPDM/Nitrile
Maximum Operating Pressure:
250 PSI
Valve Configuration:
No Relief Valve



SERIES 1 | 111A035F11CA

Body Material:
Brass
Port Size:
NPT 3/8"
Flowrate (GPH) / (LPH)
100 / 300
Sealing Material:
EPDM/Nitrile
Maximum Operating Pressure:
150 PSI
Valve Configuration:
Balanced- External Adjust



SERIES 1 | 111A100F11AA NSF

Body Material:
Brass
Port Size:
NPT 3/8"
Flowrate (GPH) / (LPH)
100 / 300
Sealing Material:
EPDM/Nitrile
Maximum Operating Pressure:
150 PSI
Valve Configuration:
Standard-Non External Adjust



SERIES 1 | 111A140F11AA

Body Material:
Brass
Port Size:
NPT 3/8"
Flowrate (GPH) / (LPH)
140 / 425
Sealing Material:
EPDM/Nitrile
Maximum Operating Pressure:
150 PSI
Valve Configuration:
Standard-Non External Adjust



SERIES 2 | 112A035F11CA

Body Material:
Brass
Port Size:
NPT 3/8"
Flowrate (GPH) / (LPH)
35 / 100
Sealing Material:
EPDM/Nitrile
Maximum Operating Pressure:
150 PSI
Valve Configuration:
Balanced- External Adjust



SERIES 2 | 112A125F11XX NSF

Body Material:
Brass
Port Size:
NPT 3/8"
Flowrate (GPH) / (LPH)
125 / 375
Sealing Material:
EPDM/Nitrile
Maximum Operating Pressure:
250 PSI
Valve Configuration:
No Relief Valve



SERIES 2 | 112A140F11XX

Body Material:
Brass
Port Size:
NPT 3/8"
Flowrate (GPH) / (LPH)
140 / 425
Sealing Material:
EPDM/Nitrile
Maximum Operating Pressure:
250 PSI
Valve Configuration:
No Relief Valve



SERIES 4 | 114B240F11BA

Body Material:
Brass
Port Size:
NPT 1/2"
Flowrate (GPH) / (LPH)
240 / 725
Sealing Material:
EPDM/Nitrile
Maximum Operating Pressure:
150 PSI
Valve Configuration:
Standard-Non External Adjust



SERIES 4 | 114B240F11XX NSF

Body Material:
Brass
Port Size:
NPT 1/2"
Flowrate (GPH) / (LPH)
240 / 725
Sealing Material:
EPDM/Nitrile
Maximum Operating Pressure:
250 PSI
Valve Configuration:
No Relief Valve



SERIES 4 | 114B330F11XX NSF

Body Material:
Brass
Port Size:
NPT 1/2"
Flowrate (GPH) / (LPH)
330 / 1000
Sealing Material:
EPDM/Nitrile
Maximum Operating Pressure:
250 PSI
Valve Configuration:
No Relief Valve



SERIES 3 | 103A140F31RA

Body Material:
Stainless Steel
Port Size:
NPT 3/8"

Flowrate (GPH) / (LPH)
140 / 425

Sealing Material:
EPDM/Nitrile

Maximum Operating Pressure:
150 PSI

Valve Configuration:
Standard-Non External Adjust


SERIES 3 | 113A035F31CA NSF

Body Material:
Stainless Steel
Port Size:
NPT 3/8"

Flowrate (GPH) / (LPH)
35 / 100

Sealing Material:
EPDM/Nitrile

Maximum Operating Pressure:
150 PSI

Valve Configuration:
Balanced- External Adjust


SERIES 3 | 113A140F31BA NSF

Body Material:
Stainless Steel
Port Size:
NPT 3/8"

Flowrate (GPH) / (LPH)
140 / 425

Sealing Material:
EPDM/Nitrile

Maximum Operating Pressure:
150 PSI

Valve Configuration:
Standard-Non External Adjust


SERIES 5 | 115B190F31BA NSF

Body Material:
Stainless Steel
Port Size:
NPT 1/2"

Flowrate (GPH) / (LPH)
190 / 575

Sealing Material:
EPDM/Nitrile

Maximum Operating Pressure:
150 PSI

Valve Configuration:
Standard-Non External Adjust


SERIES 5 | 115B265F31BA NSF

Body Material:
Stainless Steel
Port Size:
NPT 1/2"

Flowrate (GPH) / (LPH)
265 / 800

Sealing Material:
EPDM/Nitrile

Maximum Operating Pressure:
150 PSI

Valve Configuration:
Standard-Non External Adjust


SERIES 5 | 115B330F31XX NSF

Body Material:
Stainless Steel
Port Size:
NPT 1/2"

Flowrate (GPH) / (LPH)
330 / 1000

Sealing Material:
EPDM/Nitrile

Maximum Operating Pressure:
250 PSI

Valve Configuration:
No Relief Valve




Find Out More About Our Products.

Visit Our Website At:
www.proconrotarypumps.com

Have A Question?
sales@proconrotarypumps.com





www.proconrotarypumps.com

Send all inquires to:
sales@proconrotarypumps.com

PREMIUM FLUID CONTROL SOLUTIONS



PLACE DISTRIBUTOR INFORMATION HERE

138-13085 Yonge St. BLDG 19
Richmond Hill, Ontario
L4E 0K2 - Canada
T +1 800-936-2819